



# *Flatwork Finishers*

- **Frequency-controlled Motor**
- **Suspended Roll**
- **Nomex Ironing Belts**
- **Finger Guards**
- **Safety Handle**
- **Optimized Exhaust System**
- **Heavy Duty Steel Frame**
- **Polished Steel Cylinders**



**3** YEAR  
LIMITED  
WARRANTY

Huebsch's full range of heated cylinder flatwork finishers are built to meet the needs of hotels, nursing homes, hospitals and on premises laundries. Easy to operate, these flatwork finishers will save you in labor and energy costs, and their smart design is a space saver as well!



# Flatwork Finisher Specifications

## Key Product Features

- Huebsch now offers a full range of heated cylinder flatwork finishers that are simple to operate, will save you in labor and energy costs, and their smart design is a space saver as well!

- These new finishers are built to meet all the needs of hotels, nursing homes, hospitals, and on premises laundries. They are designed to boost the efficiency and productivity of each laundry operation.



- All models are equipped with a frequency-controlled motor, suspended roll, Nomex ironing belts, finger guards, a safety handle in case of power failure, easy access to all components, and an optimized exhaust system.

- All Huebsch finishers are constructed of heavy duty steel frames and thick polished steel cylinders, and are backed by a one year warranty.

Models	UD08F055	UD13F063	UD13F078	UD20F075	UD20F098	UD20F126
Roll Diameter - in (mm)	8" (200)	13" (325)	13" (325)	20" (500)	20" (500)	20" (500)
Finishing Width - in (mm)	55" (1400)	63" (1600)	78" (2000)	75" (1900)	98" (2500)	126" (3200)
Ironing Speed - ft/m (m/m)	3-15 (1-4.5)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)	3-30 (1-9)
Overall Dimensions* L" x D" x H" - in (mm)	74" x 17.5" x 43.7" (1880 x 445 x 1110)	86" x 26" x 43.8" (2192 x 661 x 1113)	100.1" x 26" x 43.8" (2542 x 661 x 1113)	117.1" x 42.2" x 46.1" (2975 x 1072 x 1171)	140.7" x 42.2" x 46.1" (3574 x 1072 x 1171)	168.3" x 42.2" x 46.1" (4275 x 1072 x 1171)
Roll Motor - HP (kW)	.33 (.25)	.33 (.25)	.33 (.25)	.5 (.37)	.5 (.37)	.5 (.37)
Roll Exhaust Motor - HP (kW)	1 x .12 (.09)	2 x .16** (2 x .12**)	2 x .16 (2 x .12)	2 x .34*** (2 x .25***)	2 x .34 (2 x .25)	2 x .34 (2 x .25)
Roll Exhaust Duct - in (mm)	1 x 3.25" (83)	2 x 4"*** (2 x 98**)	2 x 4" (2 x 98)	2 x 6"**** (2 x 150****)	2 x 6" (2 x 150)	2 x 6" (2 x 150)
<b>Gas Heating</b>						
Maximum Gas Input - Btu (kW)	N/A	76,792 (23)	102,340 (30)	136,453 (40)	167,623 (55)	235,495 (69)
Gas Inlet - in (mm)	N/A	3/4" (14)	3/4" (14)	1" (22)	1" (22)	1" (22)
Electrical Requirements • Circuit Breaker	N/A N/A N/A	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6	120/60/1 • 15 230/50/3 • 6 400/50/3 • 6
<b>Electric Heating</b>						
Capacity Resistances - HP (kW)	14 (10.5)	21 (16)	27 (20)	42 (31.5)	54 (40.5)	72 (54)
Electrical Requirements • Circuit Breaker	208-240/60/3 • 40 230/50/3 • 40 400/50/3 • 25	208-240/60/3 • 50 230/50/3 • 50 400/50/3 • 32	208-240/60/3 • 63 230/50/3 • 63 400/50/3 • 40	208-240/60/3 • 100 230/50/3 • 100 400/50/3 • 63	208-240/60/3 • 125 230/50/3 • 125 400/50/3 • 63	208-240/60/3 • 163 230/50/3 • 163 400/50/3 • 100
<b>Steam Heating</b>						
Steam Inlet - in (mm)	N/A	N/A	N/A	3/4" (19.5)	3/4" (19.5)	3/4" (19.5)
Condensate Return - in (mm)	N/A	N/A	N/A	1/2" (12.7)	1/2" (12.7)	1/2" (12.7)
Hourly Consumption - lb/hr (kg/hr)	N/A	N/A	N/A	110 (50)	147 (67)	187 (85)
Min.-Max. Steam Pressure - Psi (bar)	N/A	N/A	N/A	145 (10)	145 (10)	145 (10)
Electrical Requirements • Circuit Breaker	N/A N/A N/A	N/A N/A N/A	N/A N/A N/A	120/60/1 • 15 230/50/3 • 4 400/50/3 • 4	120/60/1 • 15 230/50/3 • 4 400/50/3 • 4	120/60/1 • 15 230/50/3 • 4 400/50/3 • 4
Shipping Weight - lb (kg)	418 (190)	1320 (599)	1474 (669)	2167 (984)	2796 (1269)	3421 (1553)
Approvals	ETL, CE	CSA, ETL, CE	CSA, ETL, CE	CSA, ETL, CE	CSA, ETL, CE	CSA, ETL, CE

\* Removal of trays will allow 22" door access on all models

\*\* One motor on electric models