SUPER LAUNDRY

Huebsch

Shepard St, Ripon, WI 54971 Telephone: 1-800-55

Softmount Extractors

- **Microprocessor with 39 Preprogrammed Cycles**
- **Heavy Duty Interior Suspension System**
- **Variable Speed Drive**
- **Programmable Spin Speeds**
- **Stainless Steel Construction**
- **Easy Installation**

Equipped with state-of-the-art and energy savings features, these machines are available in 18,25,35,55,75 and 100 lb capacities.

3 Year Limited Warranty

On-Premises Softmount Washer-Extractor Specifications

		HX18	HX25	HX35	HX55	HX75	HX100
Capacity - lb (kg)		18 (8)	25 (11)	35 (16)	55 (25)	75 (34)	100 (45)
Width - in (mm)		26" (660)	26" (660)	30 7/8" (783)	35 7/16" (900)	41 3/4" (1060)	47 1/4" (1200)
Depth - in (mm)		30 3/4" (780)	34 1/4" (870)	37 13/16" (960)	40" (1016)	46" (1168)	52 3/8" (1330)
Height - in (mm)		40 5/8" (1031)	40 5/8" (1031)	47" (1194)	60 13/16" (1544)	61 7/16" (1560)	75 5/8" (1920)
Cylinder Diameter - in (mm)		20 7/8" (530)	20 7/8" (530)	25 5/8" (650)	29 9/16" (750)	33 1/2" (850)	38 5/8" (980)
Cylinder Depth - in (mm)		13 5/8" (345)	17 3/8" (440)	19 11/16" (500)	20 7/8" (530)	21 3/16" (537)	23 1/2" (597)
Cylinder Volume - cu. ft. (liters)		2.7 (76)	3.4 (97)	5.9 (167)	8.3 (234)	10.8 (305)	15.9 (451)
Door Opening Size - in (mm)		11 13/16" (300)	11 13/16" (300)	11 13/16" (300)	15 9/16" (395)	15 9/16" (395)	19 11/16" (500)
Door Bottom to Floor - in (mm)		11" (279)	11" (279)	15 9/16" (395)	22" (559)	22" (559)	25 9/16" (648)
Wash Speed - RPM		10-50	10-50	10-50	10-50	10-50	10-50
Distribution Speed - RPM		82	82	74	69	65	61
Extract Speed - RPM		85-1000	85-1000	100-1000	250-1000	250-1000	250-800
Extract G-Force - RPM		19-296	19-296	23-36	26-418	30-475	34-350
Water Inlet Conn. - in (mm)		3 x 3/4" (19)	3 x 3/4" (19)	3 x 3/4" (19)	3 x 3/4" (19)	3 x 3/4" (19)	4 x 3/4" (19)
Steam Inlet Conn. - in (mm)		N/A	N/A	N/A	7/16" (10)	7/16" (10)	7/16" (10)
Drain Connection Size - in (mm)		2" (51)	2" (51)	2" (51)	3" (76)	3" (76)	3" (76)
Motor Size - HP (kW)		1 (3/4)	1 (3/4)	2 (1 1/2)	4 (3)	5.4 (4)	7.4 (5 1/2)
Voltage/Hz/Phase Circuit Breaker-FLA	X	200-240/50-60 1/3 • 15-6	200-240/50-60 1/3 • 15-6	200-240/50-60 1/3 • 15-12	200-240/50-60 1/3 • 15-12	N/A	N/A
	Q	N/A	N/A	N/A	N/A	200-210/50-60/3 • 20-12	200-210/50-60/3 • 25-17
	P	N/A	N/A	N/A	N/A	380-415/50-60/3 • 16-12	380-415/50-60/3 • 20-17
	N	440-480/50-60/3 • 15-6	440-480/50-60/3 • 15-6	440-480/50-60/3 • 15-12	440-480/50-60/3 • 15-12	440-480/50-60/3 • 25-17	440-480/50-60/3 • 25-20
Shipping Dimensions - in (mm)	H	44 15/16" (1140)	48 13/16" (1240)	51 5/8" (1310)	65" (1650)	68 1/8" (1730)	79 3/16" (2010)
	W	28 13/16" (732)	28 13/16" (732)	33 1/2" (850)	40 3/16" (1020)	45 11/16" (1160)	51 3/16" (1300)
	D	32 3/4" (832)	37 7/16" (950)	43 5/16" (1100)	45 5/16" (1150)	48 7/16" (1230)	56 5/16" (1430)
Net Weight - lb (kg)		520 (236)	531 (241)	765 (347)	1247 (570)	1907 (865)	3351 (1520)
Shipping Weight - lb (kg)		624 (283)	639 1/2 (290)	1030 (467)	1380 (630)	2194 (995)	3741 (1697)
Agency Approvals		CE, ETL, ETLc	CE, ETL, ETLc	CE, ETL, ETLc	CE, ETL, ETLc	CE, ETL, ETLc	CE, ETL, ETLc

Note: Voltages above may require a buck-boost transfer.

Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.

© Copyright 2007 Alliance Laundry Systems LLC

Printed in the U.S.A.
Printed on paper manufactured with virgin pulp from certified sources and a minimum of 10% post-consumer recovered fiber

Quality That Lasts

Huebsch's **heavy-duty interior suspension system** absorbs out-of-balance load vibrations and eliminates the need for special foundations.

Our **variable speed drive** and programmable spin speeds provide optimum performance for any linen type. And our **high-speed extract** reduces drying time and saves energy by removing more water from the load compared to rigid-mount models.

User-Friendly Controls

Huebsch's **state-of-the-art microprocessor control** offers 39 preprogrammed cycles and allows for 99 cycles in total. The control offers temperature-controlled fills and thermal cool-down for optimum chemical performance and improved linen protection.

Unmatched Warranty

Three-Year/Five-Year Limited Warranty — Huebsch HX model washer-extractors are covered by a THREE-year limited warranty* on all parts. The frame, basket, shaft, bearings and seals are under warranty for FIVE years*.

* Parts only, labor not included. See Huebsch Warranty Bond for specifics.

3 year limited warranty*

Alliance Laundry Systems, Shepard Street, Ripon, WI 54971 Telephone: 1-800-553-5120

135 & 165 lb On-Premises Softmount Washer-Extractor Specifications

User-Friendly Controls

Huebsch's **state-of-the-art microprocessor control** offers 39 preprogrammed cycles, and allows for 99 cycles in total. The control offers temperature-controlled fills and thermal cool-down for optimum chemical performance and improved linen protection.

Quality That Lasts

Huebsch's **heavy-duty interior suspension system** absorbs out-of-balance load vibrations and eliminates the need for special foundations.

Our **variable-speed drive** and programmable spin speeds provide optimum performance for any linen type. And our **high-speed extract** reduces drying time and saves energy by removing more water from the load compared to rigid-mount models.

Unmatched Warranty

Three Year/Five Year Limited Warranty — Huebsch HX model washer-extractors are covered by a **THREE**-year limited warranty* on all parts, and the frame, basket, shaft, bearings, and seals are under warranty for **FIVE** years*.

* Parts only, labor not included. See Huebsch Warranty Bond for specifics

3 year limited warranty*

HX Models		HX135	HX165
Capacity - kg (lb)		61 (135)	75 (165)
Width - mm (in)		1200 (47 5/16")	1300 (51 13/16")
Depth - mm (in)		1500 (59 1/8")	1620 (63 13/16")
Height - mm (in)		1920 (75 5/8")	2100 (82 5/8")
Cylinder Diameter - mm (in)		980 (38 5/8")	1095 (43 1/8")
Cylinder Depth - mm (in)		775 (30 1/2")	775 (30 1/2")
Cylinder Volume - liters (cu. ft.)		585 (20.7)	730 (25.8)
Door Opening Size - mm (in)		500 (19 5/8")	622 (24 1/2")
Door Bottom to Floor - mm (in)		648 (25 1/2")	710 (28")
Wash Speed - RPM		10-50	10-50
Distribution Speed - RPM		61	100
Extract Speed - RPM		250-800	250-750
Extract G-Force - RPM		34-350	344
Water Inlet Connection - mm (in)		4 x 19 (3/4")	3 x 25 (1") 1 x 19 (3/4")
Steam Inlet Connection - in		1/2"	3/4"
Drain Connection Size - mm (in)		76 (3")	2 x 76 (3")
Motor Size - HP (kW)		10 (7.5)	15 (11.5)
Electric Heating - kW		27	N/A
Voltage/Hz/Phase Circuit Breaker	Q	200-240/50-60/3 • 30-17	200-240/50-60/3 • 40-25
	P	380-415/50-60/3 • 25-17	380-415/50-60/3 • 25-20
	N	440-480/50-60/3 • 25-17	440-480/50-60/3 • 25-20
Shipping Dimensions - mm (in)	H	2110 (79 1/8")	2300 (90 5/8")
	W	1300 (51 3/16")	1450 (57 1/8")
	D	1630 (64 3/16")	1720 (67 7/8")
Net Weight - kg (lb)		1645 (3626)	2100 (4630)
Shipping Weight - kg (lb)		1822 (4017)	2319 (5113)
Agency Approvals		CE, ETL	CE, ETL

Note Voltages above may require a buck boost transfer.

Due to continuous product improvements, design and specifications are subject to change without notice. The quality management systems at all Alliance Laundry Systems manufacturing facilities are registered as ISO 9001:2000 compliant.

©Copyright 2007 Alliance Laundry Systems LLC