

Speed Queen®

Shepard Street, Ripon, WI 54971 1-800-345-5649

Hardmount Extractors

- Heavy duty construction, durable for years to come
- Low water usage, designed to save water and energy
- Durable stainless steel cabinet front, sides and top
- Large door opening makes loading and unloading easy
- Self cleaning, multi-compartment dispenser automatically dispenses detergent for pre-wash and main wash and fabric softener for final rinse



Hardmount washer-extractors are the standard in industries such as hotels and health care facilities, where laundries are located on the ground floor. These units are secured to the concrete floor, cost significantly less than their softmount counterparts and have a proven record of reliability with superior wash results. Speed Queen, however, delivers more than just clean results with its SC model line, which includes 20, 30, 40, 60, 80 and 125 lb units. We understand the demands of an on-premises laundry also include quality fabric care to extend linen life, efficient use of water and utilities and maximum productivity of staff.

Speed Queen durability

A heavy-duty Gamma A-Frame design increases its stability. Our rugged steel cabinet and top construction resists corrosion, while also contributing to the unit's proven reliability. Heavy-duty bearings and trunnions help SC models deliver years of reliable performance.

Wide door openings

Doors on the SC are sized to help staff make short work of the often time-consuming tasks of loading and unloading. The quicker your machines are unloaded, the sooner they're ready for the next load — a major benefit to throughput volumes.

Simple chemical dispensing

A self-cleaning, multicompartment dispenser automatically adds detergent for prewash and main wash as well as fabric softener. In addition, tubing and electrical connections accommodate liquid central supply systems for greater convenience and improved productivity.

Ease of serviceability

Removable tops and front panels limit downtime by giving owners or service personnel access to the SC's major components such as drain valves. Adding to the serviceability is the simple key entry to the top lid, while competing models require tools to perform the same task.

Excellent efficiency

SC washer-extractors equipped with the MicroMaster2 control can keep water consumption as low as 1 gallon per pound. By comparison, older units and some competing models can use as much as 2 to 3 gallons of water per pound. The end result is a more efficient on-premises laundry.



Hardmount Washer-Extractor Controls

MicroMaster2

Speed Queen's MicroMaster2 control is the industry standard for owners seeking the utmost com-



mand of their laundry operation. Customizable cycles and advanced control properties help managers adapt their process to meet any future changes. MicroMaster2 features: 30 programs, all of which can be customized; rapid advance to jump the cycle to the end, add forgotten items and restart the machine where it left off; and a half-speed wash for delicates ensures they receive the gentle care they require.

B-Micro

Speed Queen's B-Micro control



offers eight pre-programmed cycles that can be customized to meet your laundry's needs.

Three programmable water levels give managers greater control of water efficiency to lower operating expenses.

Standard

This control is defined by its straightforward design and for producing solid cleaning results through four preset wash formulas.



Specifications

Hardmount Washer-Extractors Specifications

	SC20	SC30	SC40	SC60	SC80	SC125	
Capacity - lb (kg)	20 (9)	30 (13.6)	40 (18)	60 (27)	80 (36)	125 (56.7)	
Cylinder Diameter - in (mm)	21" (533)	24" (610)	26 1/4" (667)	30" (762)	36" (914)	42" (1067)	
Cylinder Depth - in (mm)	13 3/4" (349)	16" (406)	20 1/4" (514)	22" (559)	22" (559)	24" (610)	
Cylinder Volume - cu.ft. (liters)	2.76 (78.1)	4.19 (118)	6.3 (180)	9.0 (255)	12.4 (354)	19.20 (544)	
Width - in (mm)	26" (660)	29" (737)	30 5/8" (778)	34 1/16" (865)	41 1/2" (1054)	48" (1219)	
Depth* - in (mm)	29 13/16" (757)	34 13/16" (884)	40 3/16" (1021)	42 15/16" (1091)	52" (1321)	56 3/4" (1441)	
Height - in (mm)	42 7/8" (1089)	45 7/8" (1165)	47 7/8" (1216)	50 13/16" (1291)	56 7/8" (1444)	70 1/2" (1791)	
GFactor (High Extract)	2-spd	83.1	73.3	89.9	93.8	N/A	N/A
	V-spd	N/A	N/A	40/85/140	40/85/140	40/85/140	40/85/140
Weight - lb (kg)	353 (160)	496 (225)	686 (311)	811 (368)	1346 (610)	2301 (1044)	
Shipping Weight - lb (kg)	373 (169)	519 (235)	710 (322)	838 (380)	1420 (644)	2384 (1081)	
Agency Approval	ETL _{US} , CE	ETL _{US} , CE	ETL _{US} , CE	ETL _{US} , CE	ETL _{US}	ETL _{US}	

*Overall Depth includes drain pipe and door handle.